

	contains	m <sup>2</sup>	ft <sup>2</sup>	weight
1 pack cadenza	9 planks	2,66 m <sup>2</sup>	28.67 ft <sup>2</sup>	19,4 kg
1 pallet cadenza	56 packs	149,16 m <sup>2</sup>	1605.60 ft <sup>2</sup>	1098 kg

## product specifications

dimensions mm / inch	1383 x 214 mm / 54.45" x 8.43"
total thickness mm / inch	8 mm / 0.31"
bevels	4
loc system	duoloc
level of use according to European standard EN10874	23 heavy domestic use
	32 general commercial use
residential warranty	20 years
commercial warranty	3 years

## composition

surface layer	direct laminated paper, impregnated with melamine resin
substrate	moisture resistant High Density Fiberboard (HDF)
backing	direct laminated paper, impregnated with melamine resin

## test results

abrasion resistance	EN13329	AC4 (IP≤4000)
impact resistance	EN13329	Small ball : ≤ 12 N - Big ball : ≤ 750 mm
thickness swelling	EN13329	≤ 18 %
fire resistance	EN14041	Cfl-S1
formaldehyde emission	EN14041	E1
slip resistance	EN14041	DS
density	EN323	900 kg/m <sup>3</sup>
resistance to staining	EN438	5 (groups 1+2); 4 (group 3)
effect of a furniture leg	EN424	no damage (foot type 0)
effect of a castor chair	EN425	no change in appearance or damage
thermal resistance in combination with underlay Excellence Plus	ISO 8302	0,08 m <sup>2</sup> K/W – Suitable for floor heating/cooling. Detailed instructions on <a href="http://www.berryalloc.com">www.berryalloc.com</a>



\*Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions)

